



Tyvek.

DUPONT™ TYVEK® COMMERCIAL WRAP CAPS

THE WRAP CAP SCREW FOR COMMERCIAL STEEL STUD APPLICATIONS



Why use a DuPont™ Tyvek® Commercial Wrap Cap with a screw? Quality contractors and installers have been asking for an easy way to secure Tyvek® products to steel studs. They also asked for increased holding power. We designed the DuPont™ Tyvek® Commercial Wrap Cap Screw as the solution for quality commercial and steel stud installations.

GENERAL DESCRIPTION AND APPLICATION

- A full drill point screw with an attached 2" plastic cap for use in steel stud applications (12 gauge to 20 gauge)
- Recommended for fastening any Tyvek® product—ideal for commercial applications
- Wrap Cap Screws with a 2" plastic disc reduce the potential for jobsite blow-off of wrap—delivering increased fastener holding power over traditional 1" plastic and metal caps

PRODUCT SPECIFICATIONS

Product	Type	Screw Length	Box Count	Box OD (lwd)	Weight Each
2" Dia. Wrap Cap Screws	Hand Drive or Electric Drive	1 3/4"	1000	12"x 12" x 14"	14.5 lb

FEATURES AND BENEFITS

1 3/4" Steel Stud Screw

- Can be applied by hand or drill
- Self-tapping drill point screw, #8 shank with a modified truss head style (Phillips head)
- Screws are coated with an organic fluoropolymer for improved rust protection
- Drill bit included in each box, for ease of installation
- Screws are ore-attached to Wrap Caps for quick installation

2" Wrap Cap

- Constructed of high-density polyethylene with UV inhibitors
- Large diameter cap increases fastener holding power—reducing the potential for job-site blow-off of wrap
- Large plastic cap provides additional protection around fastener penetrations
- Large diameter cap permits easy handling and installation

PRODUCT GUARANTEE

DuPont will replace any Tyvek® product damaged during installation by weather or normal handling if it is installed according to procedures published by DuPont. If you have any questions, call DuPont Tyvek® at 1-800-44-TYVEK®



For more information visit us at www.weatherization.tyvek.com or call 1-800-44-Tyvek